



CRETO™
Worldwide Inc.
Permanent as The Pyramid

Concrete & Wood Preservers Energy Coatings

CRETO Deep Clean

Product Description

CRETO® Deep Clean concentrate is a fortified concrete and multipurpose cleaner that is designed to clean and "etch" the surface simultaneously. Oils, dirt, efflorescence, and grime are removed.

Characteristics & Advantages

- **Heavy Duty** industrial strength, yet, easy to use
- **Easily cleans up with water**
- **Can be used as a Non-toxic** replacement for more environmentally and ecologically unfriendly products
- **Can be diluted** for a multitude of cleaning applications

Typical uses

- Removing oils, grease, stains, dirt and contaminated surface residues
- Preparing and "etching" a surface prior to application of a subsequent coating
- Daily cleaning applications which require a strong cleaner which will be effective, non-toxic and environmentally friendly.

Surface Preparation

The surface to be cleaned should be free of any loose dirt or materials in order to present a bare surface ready prior to applying Deep Clean. Cleaning with a stiff broom followed by hosing off of any remaining loose dirt is recommended.

Safety

Refer to the CRETO® Deep Clean Material Safety Data Sheets regarding hazards and personal protection. In case of accidental contact with the skin or eyes, flush thoroughly with clean water.

General Application Instructions

1. Deep Clean can be used full strength for some industrial applications where muriatic or acetic acid wash might normally be used.
2. Can be diluted to various strengths depending on the application for which it is intended to be used.

3. Pre-wetting the surface to be cleaned can sometimes aid the penetration of the Deep Clean in that it opens the pores of the surface being cleaned.

Applicators Please Note:

1. Some surfaces can be damaged by a full strength application of CRETO® Deep Clean.
2. Always test a small patch area at various concentrations, on pre-wetted and non-pre-wetted surfaces, to determine the most effective dilution ratios/concentration for each specific application.

Note: This is especially important for architectural surfaces which can be sensitive to cleaners.

3. Apply CRETO® Deep Clean to the most heavily saturated or hard to clean areas first.
4. Apply Deep Clean thereafter as needed, spread and brush in with a stiff broom, allowing Deep Clean to "etch" the surface for about 30 minutes.
5. **Do not allow Deep Clean to dry out during these 30 minutes.** If it starts to dry out, apply a fine spray of water as necessary to keep the Deep Clean wet.
6. **Pay close attention during this 30 minutes** to ensure that no visible damage to surfaces is occurring during the cleaning process. If so rinse with water immediately.
7. Rinse with clean water. Continue rinsing until no visible suds appear. Using high pressure washers can speed up the rinsing process.

Exterior Applications

Apply CRETO® Deep Clean generously over the surface by pouring, spraying, etc. Use a stiff broom or scrubbing machinery to lightly agitate and scrub product into the surface. Allow to "etch" for about 30 minutes. Rinse with clean, high pressure water.



CRETO™
Worldwide Inc.
Permanent as the Pyramid

Concrete & Wood Preservers Energy Coatings

Interior Applications

Interior cleaning is usually carried out in a much more controlled manner. Normally, Deep Clean would be applied much more sparingly to facilitate easier clean-up, unless a high pressure sprayer can be used, mop and rinse applied areas in a normal manner.

Clean Up

Clean brushes and other application equipment or containers with water.

Note: In cases where there is an environmental concern regarding the rinse run-off, (i.e. If the rinse run-off will be going down a drain), it is always recommended to neutralize the alkali content of the rinse water with a light application of a mildly acidic solution or powder, (i.e. Oxilic acid) prior to flushing and rinsing will be sufficient.

Packaging

- 1 gallon jug
- 5 gallon pail

Limitations

CRETO® Deep Clean should not be applied if the surface temperature is below freezing.

Buyers and users should refer to the CRETO® Material Safety Data Sheet for Deep Clean prior to application on any surface.

Disclaimer

CRETO® Engineered Solutions, and CRETO Worldwide inc., believe this information to be true to the best of our knowledge and our products are of the highest quality and uniform within manufacturing tolerances.

Since no control is exercised over product use, no warranty, expressed or implied, is made as to the suitability of the product for a particular use or as to the effect of such use, and no liability is assumed, directly or indirectly.

Buyers and users are encouraged to conduct their own small scale tests prior to application.